

Manufacturer: Procalçado - Produtora de Componentes para Calçado, S.A.
Largo das Alminhas das Barrancas, 97
4415-343 - Pedroso – V. N. de Gaia, PORTUGAL

General Requirements: Directive 89/686/EEC – category 1

Model: CLOG

Description: Clog marked WOCK®, entirely made of polymeric materials, with two colors and a black antistatic insert, with strap and removable Steri-Tech® Clog insole.

Size range: from 35/36 to 47/48

Intended use: Hospitals and other Healthcare Institutions; Cosmetics/Beauty Companies; Pharmaceutical Industry; Operation Room.



Technical standard: EN ISO 20344:2011 - Personal protective equipment – Test methods for footwear
EN ISO 20347:2012 - Personal protective equipment – Occupational footwear

Technical features: Specific ergonomics features: EN ISO 20347:2012/5.3.3 / EN ISO 20344:2011/5.1
Thickness of upper: EN ISO 20347:2012/5.4.2 / EN ISO 20344:2011/6.1
Tensile properties of upper: EN ISO 20347:2012/5.4.4 / EN ISO 20344:2011/6.4
Flexing resistance of upper: EN ISO 20347:2012/5.4.5 / EN ISO 20344:2011/6.5
Tear strength of outsole: EN ISO 20347:2012/5.8.2 / EN ISO 20344:2011/8.2
Abrasion resistance of outsole: EN ISO 20347:2012/5.8.3 / EN ISO 20344:2011/8.3
Flexing resistance of outsole: EN ISO 20347:2012/5.8.4 / EN ISO 20344:2011/8.4
Antistatic footwear: EN ISO 20347:2012/6.2.2.2 / EN ISO 20344:2011/5.10
Energy absorption of seat region: EN ISO 20347:2012 / 6.2.4 / EN ISO 20344:2011/5.14
Slip resistance (dry and wet): SATRA TM144:2011

Additional information: Washability at 90°C: SATRA TM 158:1992
Sterilization in Autoclavable after 5 cycles of 15 minutes at 134°C

Additional notes: WOCK® clog Walksoft Insole (sold separately) cannot be washed or sterilized in an autoclave; clogs lose their anti-static properties when insoles are worn.



Grijó, V. N. de Gaia, Portugal – March 2017

Managing Director